

**CD-9361 SONY Indoor/Outdoor
Day/Night Long-Range Infrared
Varifocal 700 TVL Camera**



Installation Manual

Outdoor Varifocal Hi-Res Day/Night
Infrared CCD Bullet Camera

Camera Installation

1. Camera Mounting:

Items Needed:

Screwdriver, Drill, Mounting Hardware (not included), Pencil

2. Mark the bolt holes and attach bracket to wall



3. Loosen the adjustments and position camera as desired.



Camera Installation

4. Adjust Zoom and Focus with adjustment knobs on the bottom of the camera.

Note: You must adjust both together



5. Adjust advanced camera settings with the OSD Controls on the camera's cable.



Platinum CCTV Surveillance Solutions

CD-9361 Long Range IR CCD Camera	
Image Sensor	1/3" SONY EXView II CCD
Number of Pixels	NTSC: 976 (H) x 494 (V)
Scanning System	15.7343Khz (H), 60 Hz (V)
Sync System	Internal Synchronization
Resolution	700 TVL
Lens	2.8-12mm Varifocal Lens
Video Output	1.0Vp-p75Ω
S/N Ratio	>52dB
Shutter Time	1/60-1/100,000 Sec.
Operation Temp.	-20°C ~ +50°C
Storage Temp.	-30°C ~ +60°C
Useable Illumination	0.001 Lux (F:2.0), 0 Lux (IR On)
Power Source	DC 12V 800mA

Installation Notes

- For Indoor or Outdoor Use
- Disassembly of camera will void warranty
- Remove protective film from lens before use
- Handle with care
- Never touch lens directly
- Clean the lens occasionally with a dry micro-fiber cloth, or plastic cleaner only – Do not use abrasive-type cleaners as they will scratch lens