

PTZ-2000-10 Hi-Res Outdoor Home/Business Mini-PTZ Dome Security camera with 100x Zoom



Camera Features

- CCD Image Technology
- High Speed Pan/Tilt/Zoom
- 10x Optical Zoom
- 1/4" Format Sony CCD Image Sensor
- 480 TV Lines Resolution
- **Low Light Night Vision**
- Weatherproof IP 66 Rating
- Durable Housing
- Wall Mount included

The **PTZ-2000-10** is a great selection for any home or business security camera installation where a moving Pan/Tilt/Zoom camera is required but smaller size is preferred. This camera has high speed movement capabilities, in a small 4" dome body.

The **PTZ-2000-10** features a high resolution 480 line Sony CCD sensor providing great color reproduction and sensitivity with a signal-to-noise (S/N) ratio of more than 46 dB.

With the included wall mount bracket, this camera can be easily mounted on any indoor or outdoor wall for your home or business security camera installation.

The **PTZ-2000-10** camera has great low-light night vision up to 0.01 Lux for optimum picture quality even in lower light camera installations.

MODELS

PTZ-2000-10

High Resolution 480 TVL; 10x Optical Zoom High Speed Indoor/Outdoor 4"

CAMERA

Signal Format
Scanning Frequency
Image Sensor
Effective Pixels
Horizontal Resolution
Signal to Noise Ratio
Lens
Dimensions
Focus
Maximum Sensitivity
Sync System
White Balance
Shutter Speed
Iris Control
Gain Control
Video Output
Warranty
Video Connection

NTSC (US & Japan)
15.625KHz(h)50Hz(V)
1/4" Sony CCD 480 TVL Color
NTSC = 752(H) x 582(V)
>480 TV Lines
>46 dB
10x Optical + 10x Digital Zoom
5.98" x 5.98" x 4.72"
Adjustable (Automatic)
1 Lux (Color) ~ 0.01 Lux (B/W)
Internal/External
Programmable
Programmable
Automatic w/Manual Override
Automatic w/Manual Override
1.0 +0.2Vp-p
1 Year Mfg. Parts/Labor
BNC

OPERATIONALS

Preset
Pattern
Pan Speed
Pan Rotation Range
Tilt Range
Communication

128 Preset Points
200 Second Recordable Pattern
0.2°/s to 300°/s (Zoom Proportional)
360° continuous
Tilt 90° w/ Auto Flip
Auto-Sensing RS-485 Interface

ENVIRONMENTAL

Operating Temperature
Fan/Heater
Weather Resistant
Power Supply

-35° to 55°C
Automatic Fan and Heater
IP66 Rating
AC 24V +- 5% (power supply incl)



Great Color Video and High Speed Camera Control for Home or Business Security Camera Installations

PTZ-2000-10 Hi-Res Outdoor Home/Business Mini-PTZ Dome Security camera with 100x Zoom



Camera Features

- CCD Image Technology
- High Speed Pan/Tilt/Zoom
- 10x Optical Zoom
- 1/4" Format Sony CCD Image Sensor
- 480 TV Lines Resolution
- **Low Light Night Vision**
- Weatherproof IP 66 Rating
- Durable Housing
- Wall Mount included

The **PTZ-2000-10** is a great selection for any home or business security camera installation where a moving Pan/Tilt/Zoom camera is required but smaller size is preferred. This camera has high speed movement capabilities, in a small 4" dome body.

The **PTZ-2000-10** features a high resolution 480 line Sony CCD sensor providing great color reproduction and sensitivity with a signal-to-noise (S/N) ratio of more than 46 dB.

With the included wall mount bracket, this camera can be easily mounted on any indoor or outdoor wall for your home or business security camera installation.

The **PTZ-2000-10** camera has great low-light night vision up to 0.01 Lux for optimum picture quality even in lower light camera installations.

MODELS

PTZ-2000-10

High Resolution 480 TVL; 10x Optical Zoom High Speed Indoor/Outdoor 4"

CAMERA

Signal Format
Scanning Frequency
Image Sensor
Effective Pixels
Horizontal Resolution
Signal to Noise Ratio
Lens
Dimensions
Focus
Maximum Sensitivity
Sync System
White Balance
Shutter Speed
Iris Control
Gain Control
Video Output
Warranty
Video Connection

NTSC (US & Japan)
15.625KHz(h)50Hz(V)
1/4" Sony CCD 480 TVL Color
NTSC = 752(H) x 582(V)
>480 TV Lines
>46 dB
10x Optical + 10x Digital Zoom
5.98" x 5.98" x 4.72"
Adjustable (Automatic)
1 Lux (Color) ~ 0.01 Lux (B/W)
Internal/External
Programmable
Programmable
Automatic w/Manual Override
Automatic w/Manual Override
1.0 +0.2Vp-p
1 Year Mfg. Parts/Labor
BNC

OPERATIONALS

Preset
Pattern
Pan Speed
Pan Rotation Range
Tilt Range
Communication

128 Preset Points
200 Second Recordable Pattern
0.2°/s to 300°/s (Zoom Proportional)
360° continuous
Tilt 90° w/ Auto Flip
Auto-Sensing RS-485 Interface

ENVIRONMENTAL

Operating Temperature
Fan/Heater
Weather Resistant
Power Supply

-35° to 55°C
Automatic Fan and Heater
IP66 Rating
AC 24V +- 5% (power supply incl)



Great Color Video and High Speed Camera Control for Home or Business Security Camera Installations