

**CD-9260 SONY Indoor/Outdoor
Day/Night Long-Range Infrared
Varifocal Camera**



Installation Manual

Outdoor Weatherproof Day/Night
Infrared CCD Bullet Camera

For Warranty Registration, Visit
[Http:// Platinum-CCTV.com](http://Platinum-CCTV.com)

Camera Installation

1. Camera Mounting:

Items Needed:

Screwdriver, Drill, Mounting Hardware (not included), Pencil

2. For Wall Mount bracket



- a. Assemble 2 pieces of camera support bracket and secure with 4 screws



- b. Attach support bracket to Camera body

Camera Installation

- c. Attach support bracket to camera bracket



- d. Push cable through holes in bracket



- e. For Ceiling mount bracket, simply thread bracket to camera (top or bottom)



Platinum CCTV Surveillance Solutions

| CD-9260 Long Range IR CCD Camera | |
|---|------------------------------------|
| Image Sensor | 1/3" SONY CCD |
| Number of Pixels | NTSC: 540 (H) x 491 (V) |
| Scanning System | 15.7343Khz (H), 60 Hz (V) |
| Sync System | Internal Synchronization |
| Resolution | 420 TVL |
| Lens | 4-9mm Varifocal Lens (Ext. Adjust) |
| Video Output | 1.0Vp-p75Ω |
| S/N Ratio | >52dB |
| Shutter Time | 1/60-1/100,000 Sec. |
| Operation Temp. | -20°C ~ +50°C |
| Storage Temp. | -30°C ~ +60°C |
| Useable Illumination | 0.5 Lux (F:2.0), 0 Lux (IR On) |
| Power Source | DC 12V 500mA |

Installation Notes

- For Indoor or Outdoor Use
- Disassembly of camera will void warranty
- Remove protective film from lens before use
- Handle with care
- Never touch lens directly
- Clean the lens occasionally with a dry micro-fiber cloth, or plastic cleaner only – Do not use abrasive-type cleaners as they will scratch lens